

HMT130 Temperature Transmitter

				1	2	3	4	5	6	7	8	9	10	11	12	13	14	Price	
Vaisala HUMICAP® Temperature Transmitter				HMT130	T				A	0									
Output parameters	Temperature output only																		
Transmitter type	Wall mount/fixed probe																		
	<i>Remote probe with 3 m cable</i>																		
	<i>Remote probe with 5 m cable</i>																		
	<i>Remote probe with 10 m cable</i>																		
	<i>Remote probe with 10 m cable + 10 m extension</i>																		
	<i>Remote probe with 20 m cable</i>																		
Display	No display																		
	<i>Display</i>																		
Analog output signal (RS485 also included)	0...1 V	3-wire																	
	0...5 V	3-wire																	
	0...10 V	3-wire																	
SPECIAL	Define scale:	3-wire																	
Parameter for Output 1	T	-40...+60 °C	(-40...+140 °F)																
		-20...+80 °C	(-4...+176 °F)																
		0...+60 °C	(+32...+140 °F)																
		-40...+80 °C	(-40...+176 °F)																
		0...+50 °C	(+32...+122 °F)																
SPECIAL	Define quantity		Scale																
Parameter for Output 2	None																		
Display Units	Metric																		
	Non metric																		
Sensor protection	Plastic grid																		
	Plastic grid with PTFE filter																		
	Stainless steel sintered filter (for remote probes only)																		
Transmitter installation	No accessories																		
	<i>Rain shield with installation kit (215109)</i>																		
Installation kit for probe	No accessories																		
	<i>Duct installation kit (215619)</i>																		
	<i>Probe mounting flange (226061)</i>																		
	<i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i>																		
	<i>Probe mounting clamp, 1 piece (225501)</i>																		
Cable bushings	Cable gland for 2...6 mm diameter cable																		
	Conduit fitting PG9																		
	Conduit fitting NPT 1/2"																		
	No bushing (rubber plug)																		
	<i>All bushings (includes A, B, C and D)</i>																		
PC Accessories	No																		
	<i>Service cable for PC, USB (219685)</i>																		
Operation manual	No manual																		
	Multilingual																		

Total
QTY
Total value

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130 T A 1 D